Seat Belt for Forklifts

Forklift Seat Belts - This guideline reason is to be able to describe the Regulation requirements for the application of driver seatbelts or restraints on lift trucks. It is the employers' liability to ensure that each and every machinery, piece of equipment and device inside the workplace is chosen and utilized rightly and operated in accordance with the manufacturer's instructions.

Rough Terrain lift trucks should meet the guidelines of ANSI Standard ASME B56.6-1992 in regards to their design, maintenance, inspection, fabrication and use.

Mobile equipment like side boom tractors along with a Rollover Protective Structure (ROPS), ought to have seat belts that meet the Society of Automotive Engineers Standard J386 JUN93, Operator Restraint System for Off-Road Work Machines. If whichever mobile machine includes seat belts required by law, the operator and subsequent passengers need to make certain they utilize the belts every time the motor vehicle is in motion or engaged in operation since this could cause the equipment to become unsteady and hence, unsafe.

If a seat belt or other operator restraint is needed on a lift truck.

The seat belt requirements while working a forklift depend on various factors. Whether or not the lift truck is outfitted along with a Rollover Protective Structure, the kind of lift truck itself and the year the forklift was manufactured all contribute to this determination. The manufacturer's instructions and the requirements of the applicable standard are referenced in the Regulation.

In the case of powered industrial forklifts, ANSI Standard ASME B56.1-1993 refers to a driver restraint device, enclosure or system. A driver restraint device, system, or enclosure is intended to be able to assist the operator in lessening the probability of entrapment of the torso and/or head between the truck and the ground in the event of a tip over. The system or restraint device might include a seat belt, while a seat belt is not necessarily a part of such equipment or system.